# **Compressor Lubrication**

## Manzel® HP-50™ High Pressure Lubricators

#### **Features and Benefits**

- Operating pressures to 60,000 psi for lubricating compressor and circulator cylinder walls, heavily loaded bearings and other moving parts
- Single plunger force feed design is highly efficient for injecting lubricants and/or compatible fluids into high pressure systems
- Vacuum sight feeds on self-contained pumping units show output of lubricant to individual lubrication points
- All working parts are totally enclosed and self-lubricated
- Individual pumping units easily removed for service
- Feed rate infinitely variable from minimum to maximum with simple hand adjustment

### **Typical Applications**

· Compressors and industrial equipment

#### **Typical Fluids Handled**

· Mineral or synthetic oil

### **Technical Specifications**

Number of Feeds	Max. Pressure	Reservoir Capacity (Quarts) (1)	Plunger Diameter (inches)	Drops Per Stroke		Cubic Inches Per Stoke		Cubic cm Per Stroke		Strokes Per Minute	
				Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
1-4	60,000	9	1/4	1	4	0.002	0.008	0.033	0.113	3	36

#### **Ordering Information**

HP-50 Pump					
562952	HP-50 Pump Assembly				
HP-50 Lubricator Boxes					
564276	HP-50 Lubricator without Pumps or Options				
562925	HP-50 Lubricator with 4 Pumps				
562926	HP-50 Lubricator with 2 Pumps				
562927	HP-50 Lubricator with 4 Pumps, Provision for Flange Mounted Auto Fill, and Nitrogen Purge Port				
562928	HP-50 Lubricator with 4 Pumps, Low Level and Shaft Rotation Alarm				
562929	HP-50 Lubricator with 4 Pumps, Provisions for Flange Mounted Auto Fill and Low Level in Fill Plate				
564277	HP-50 Lubricator with 4 Pumps and Steam Heater				
564278	HP-50 Lubricator with 3 Pumps and Steam Heater				
564279	HP-50 Lubricator with 4 Pumps, Provision for Flange Mounted Auto Fill, Nitrogen Purge and Shaft Rotation/Low Level Alarm on Left				

564280	HP-50 Lubricator with 4 Pumps, Provision for Flange Mounted Auto Fill, Nitrogen Purge and Shaft Rotation/Low Level Alarm on Right			
564282	HP-50 Lubricator with 4 Pumps, Shaft Rotation and Low Level Alarm			
564283	HP-50 Lubricator with 4 Lubricator Boxes with 15 Pumps, Provision for Center Mounted Motor and Base			
258262	HP-50 Lubricator with 4 Pumps and Low Level			
258263	HP-50 Lubricator with 4 Pumps, Provisions for Flange Mounted Auto Fill and Low Level in Fill Plate, and Proximity Switch Shaft Rotation Indicator on Right			
HP-50 Accessories				
563111	HP-50 plunger and cylinder			
564336	HP-50 check valve			
558881	Electric heater, 120/240 VAC			
563020	Shaft rotation alarm			
563024	Low level			

