

# LD Series Electronic Meters

## Dispense Meters and Control Valves

### Features and Benefits

- Manual and Preset Dispense
- Dispenses in gallons, quarts, pints and liters
- Easy to read LCD display with durable switches for long life
- Rugged engineered material for superior impact resistance and long life
- Ergonomically-designed handle for optimum comfort
- Standard rigid extension kit and automatic thermal compensating nozzle
- Optional extensions available

### Typical Applications

- Metered oil dispense
- Automotive dealerships
- Heavy-duty dealerships
- Fast lube centers
- Fleet service facilities
- Service shops
- For indoor use only
- In-plant

### Typical Fluids Handled

- Petroleum- and synthetic-based oils
- Anti-freeze

### Technical Specifications

Flow Range <sup>(1)</sup> .....	0.1 - 5 gpm (0.4 - 19 lpm)
Maximum Working Pressure .....	1000 psi (69 bar)
Units of measure.....	Quarts, pints, gallons, liters (factory set to quarts)
Weight .....	3 lb (1.36 kg)
Inlet .....	1/2 in npt
Outlet.....	1/2 in npt
Operating Temperature Range.....	32 - 120° F (0 - 48.8° C)
Storage Temperature Range.....	-30 - 120° F (-34.4 - 48.8° C)
Battery .....	9 volt alkaline
Battery Life.....	one year
Wetted Parts.....	sst, nitrile rubber, zinc, cs, lcp
Meter Pressure Loss <sup>(1)</sup> .....	90 psi (6.2 bar) @ 5 gpm (19 lpm)
Accuracy <sup>(2)</sup> .....	±0.5%
Dimensions (without extension) .....	11 in L x 3.25 in W x 3.25 H (28 cm L x 8.3 cm W x 8.3 cm H)
Maximum Totalizer .....	999,999 gallons or liters
Maximum Recorded Dispense.....	999.9 Units (LDP5 only)
Warranty .....	Two Years
Instruction Manual .....	312668

(1) Tested in 10W oil at 70°F. Flow rates vary with fluid pressure, temperature, viscosity, inlet fitting and nozzle type.

(2) @ 2.5 gpm (9.5 lpm) @ 70° F (21° C) with 10 wt. oil and 1 gal (3.8 l) dispensed.

May require re-calibration. Out-of-box accuracy ±1.25%. Not recommended for in-line installation.

### Ordering Information

LDM5 Manual Dispense Meters	
255751	1/2 in npt(f) swivel, flexible extension and automatic nozzle for oil and anti-freeze
256215	1/2 in npt(f) swivel, rigid extension, trigger guard/boot and automatic nozzle for oil and anti-freeze
258693	1/2 in npt(f) swivel, flexible extension, trigger guard/boot and automatic nozzle for oil and anti-freeze
LDP5 Preset Dispense Meters	
255277	1/2 in npt(f) swivel, flexible extension and automatic nozzle for oil and anti-freeze
256216	1/2 in npt(f) swivel, rigid extension, trigger guard/boot and automatic nozzle for oil and anti-freeze
258694	1/2 in npt(f) swivel, flexible extension, trigger guard/boot and automatic nozzle for oil and anti-freeze

